

옵션

FSMR 측정 리시버



	옵션 모델	설명
하드웨어	FSMR-B223	YIG Preselection w/20 dB Preamplifier, 3.6 GHz to 26.5 GHz (not w/FSMR-B23, FSMR-B223, for FSMR26)
	FSMR-B2	YIG Preselection 3.6 GHz to 50 GHz for FSMR 50 for R&S@FSMR50 only
	FSU-B4	OCXO, low aging/improved phase noise at 10 Hz carrier offset
	FSU-B9	Tracking generator 100 kHz to 3.6 GHz
	FSU-B12	Output Attenuator, 0 dB to 70 dB (requires FSU-B9)
	FSMR-B18	Removable Hard Disk
	FSMR-B19	Second Hard Disk for FSMR-B18 (requires FSU-B9)
	FSMR-B23	RF Preamplifier 3.6 GHz to 26 GHz for FSMR 26 (Req. FSU-B25, not w/FSMR-B2, FSMR-B223, for FSMR26 only)
	FSMR-B73	Vector signal analysis for FSMR
	FSU-B24	30 dB Preamplifier, 100 kHz to 50 GHz (for FSU26, FSU43, FSU46, FSU50, not for FSU50)
	FSU-B25	Electronic Attenuator, 0 dB to 30 dB, and 20 dB Preamplifier (3.6 GHz)
	FSMR-Z2	Attenuation Calibration Kit
	RT-ZA9	N(m) Adapter for R&S@RT-Zxx oscilloscope probes
	소프트웨어	FSWP-K4
FSMR-B2		YIG Preselection, 3.6 GHz to 26.5 GHz (not w/FSMR-B23, FSMR-B223, for FSMR26)
FSMR-B2		YIG Preselection, 3.6 GHz to 43 GHz (not w/FSMR-B23, FSMR-B223, for FSMR26)
FS-K15		VOR/ILS Measurement Demodulator
FS-K30		App. Firmware for Noise Figure and Gain Measurements for FSP, FSU and FSQ
FS-K40		Application Firmware for Phase Noise Measurement
FS-K5		GSM/EDGE Application Firmware
FS-K72		3GPP BTS/Node B FDD Application Firmware
FS-K73		3GPP UE FDD Application Firmware
FS-K74		3GPP HSDPA BTS Application Firmware
FS-K76		3GPP TD-SCDMA BTS Application Firmware
FS-K77		3GPP TD-SCDMA UE Application Firmware
FS-K82		CDMA2000@ / IS-95 (cdmaOne) / 1xEV-DV BTS
FS-K83		CDMA2000@/1xEV-DV MS Application Firmware
FS-K84		CDMA2000@/1xEV-DO BTS Application Firmware
FS-K85		CDMA2000@/1xEV-DO MS Application Firmware