



## Ordering data

### testo 870-1

Thermal imager testo 870-1 with integrated testo SuperResolution, including professional software, USB cable, mains unit and rechargeable Li-ion battery

Part no. 0560 8701



### testo 870-2

Thermal imager testo 870-2 in a robust case with integrated testo SuperResolution and digital camera, including professional software, USB cable, mains unit and rechargeable Li-ion battery

Part no. 0560 8702



## Accessories

	Part no.
High-quality transport case	0516 8700
Holster case	0554 7808
Spare battery. Additional Lithium ion rechargeable battery for extending operating time.	0515 5100
Battery charging station. Desktop charger for optimizing charging time.	0554 1103
Emission adhesive tape. Adhesive tape, e.g. for reflective surfaces (roll, L.: 10 m, W.: 25 mm), $\epsilon = 0.95$ , temperature resistant to +250 °C	0554 0051
ISO calibration certificates; Calibration points at 0 °C, +25 °C, +50 °C	0520 0489
ISO calibration certificates; Calibration points at 0 °C, +100 °C, +200 °C	0520 0490
ISO calibration certificates; Freely selectable calibration points in the range -18 to +250 °C	0520 0495

## Technical data

	testo 870-1	testo 870-2
<b>Infrared image output</b>		
Infrared resolution	160 x 120 pixels	
Thermal sensitivity (NETD)	<100 mK at +30 °C	
Field of view/min. focus distance	34° x 26° / <0.5 m (Fixed focus)	
Geometric resolution (IFOV)	3.68 mrad	
SuperResolution (pixel / IFOV)	320 x 240 pixels / 2.3 mrad	
Image refresh rate	9 Hz	
Focus	Fixed focus	
Spectral range	7.5 to 14 µm	
<b>Image output visual</b>		
Image size / min. focus distance	–	3.1 MP / 0.5 m
<b>Image presentation</b>		
Image display	3.5" LCD with 320 x 240 pixels	
Display options	IR image only	IR image / real image
Colour palettes	4 (iron, rainbow, cold-hot, grey)	
<b>Image presentation</b>		
Measuring range	-20 to +280 °C	
Accuracy	±2 °C, ±2 % of m.v.	
Emissivity / reflected temperature	0.01 to 1 / manual	
<b>Measuring functions</b>		
Analysis function	Centre point measurement, hot/cold spot measurement	
<b>Imager equipment</b>		
Digital camera	–	✓
Lens	34° x 26°	
JPEG storage	✓	
Full screen mode	✓	

	testo 870-1	testo 870-2
<b>Image storage</b>		
File format	.bmt and .jpg; export options in .bmp, .jpg, .png, .csv, .xls	
Memory	Internal storage (1.6 GB / >2000 images)	
<b>Power supply</b>		
Battery type	Li ion rechargeable battery exchangeable on site	
Operating time	4 hours	
Charging options	in instrument / charger (optional)	
Mains operation	yes	
<b>Ambient conditions</b>		
Operating temperature range	-15 to +50 °C	
Storage temperature range	-30 to +60 °C	
Air humidity	20 to 80 %RH non-condensing	
Housing protection class (IEC 60529)	IP54	
Vibration (IEC 60068-2-6)	2G	
<b>Physical specifications</b>		
Weight	550 g	
Dimensions (L x W x H) in mm	219 x 96 x 95	
Housing	PC - ABS	
<b>PC software</b>		
System requirements	Windows XP (Service Pack 3), Windows Vista, Windows 7, Windows 8 Interface: USB 2.0	
<b>Standards, tests, warranty</b>		
EU Directive	2004 / 108 / EG	
Warranty	2 years	

- ✓ included in delivery
- (✓) optional
- not available



## Overview of variants

Features	testo 870-1	testo 870-2
Infrared resolution	160 x 120 pixels	
Thermal sensitivity (NETD)	<100 mK at +30 °C	
Temperature range	-20 to +280 °C	
Image refresh rate	9 Hz	
Lens 34° x 26°	✓	
SuperResolution	✓	
Integrated digital camera	-	✓
Auto Hot/Cold Spot Recognition	✓	
High-quality transport case	(✓)	✓
Additional battery	(✓)	
Battery charging station	(✓)	

✓ included in delivery

(✓) optional

- not available

### (주)누비콤

#### 서울본사

서울특별시 영등포구 경인로 775(문래동 3가, 에이스하이테크시티 3동 201호)

TEL: 070-7872-0701 FAX: 02-2167-3801

E-mail: sales@nubicom.co.kr

#### 고객지원센터

TEL: 070-7872-0701, 080-801-7880 FAX: 02-2167-3802

E-mail: oft@nubicom.co.kr

#### 대전 사무소

대전광역시 유성구 대덕대로 593(도룡동 386-2) 대덕테크비즈센터 203호

TEL: 070-7872-0712 FAX: 042-863-2023

E-mail: inyeom@nubicom.co.kr